

Model No	Replace Yuasa&Other Suppliers#	Voltage(V)	Capacity(A L	W	H
DLFP4L-BS	YTX4L-BS	12.8	14	114	70 86
DLFP5Z	YTX4L-BS、 YTZ5S、 YB4L-A、 YB4L-B	12.8	38	114	70 86
DLFP5L-BS	YTX5L-BS	12.8	38	114	70 105
DLFP5L-B	12N5-3B、 12N5-4B、 12N5.5-3B、 12N5.5-4B	12.8	38	120	60 130
DLFP7ZS	YTX5L-BS、 YTX7L-BS、 YTZ7S、 YB7C-A	12.8	32	114	70 105
DLFP7B-BS	YT7B-BS	12.8	32	148	65 92
DLFP9-B	12N7-4A、 12N7-4B、 YB7-A、 12N9-4A	12.8	42	138	75 133
DLFP9L-B	12N7-3B、 12N7D-3B、 YB7L-B、 12N9	12.8	42	134	75 133
DLFP9B-BS	YT7B-BS、 YT9B-BS	12.8	42	148	65 92
DLFP9-BS	YTX7A-BS、 YTX9-BS	12.8	42	148	87 94
DLFP12B-BS	YT12B-BS	12.8	76	149	65 92*130
DLFP12-BS	YTZ10S、 YT12A-BS	12.8	76	148	87 94
DLFP12A-A	12N12A-4A-1、 YB12A-A、 YB12-B、 YB12-C	12.8	76	134	75 133*160
DLFP12AL-A	YB12AL-A、 YB12AL-A2	12.8	76	134	75 133*160
DLFP14B-BS	YT12B-BS、 YT14B-BS	12.8	64	149	65 92*130
DLFP14ZS	YTZ10S、 YT12A-BS、 YTZ12S、 YTX12-	12.8	64	149	87 94
DLFP14-A	YB10A-A2、 YTX14AH-BS、 YB14-A2、 YB14-B2	12.8	64	134	88 145*165
DLFP14L-A	YTX14AHL-BS、 YB14L-A1、 YB14L-A2、 YB14L-B2	12.8	64	134	88 145*165
DLFP14-BS	YTX14-BS	12.8	64	149	87 145
DLFP14L-BS	YTX14L-BS	12.8	64	149	87 145
DLFP16B-A	YTX16-BS-1、 HYB16A-AB、 YB16B-B1	12.8	115	149	87 94
DLFP16-BS	YTX14H、 YTX14H-BS、 YTX16-BS	12.8	115	148	87 145
DLFP20CH-BS	YB16B-A、 YTX20CH、 YTX20CH-BS	12.8	96	148	87 145
DLFP51913	51813、 51913	12.8	96	185	80 170
DLFP20-BS	YB16-B、 YB16C-B、 YB16-B-CX、 YB18-B	12.8	96	175	87 155
DLFP20L-BS	YB16L-B、 YB16CL-B、 YB16-B-CX、 YB18-B	12.8	96	175	87 155
DLFP20H-BS	YB16-B、 YB16C-B、 YB18-A、 YTX20-B	12.8	128	175	87 155
DLFP20HL-BS	YB16L-B、 YB16CL-B、 YB16HL-A-CX、 YB18-B	12.8	128	175	87 155
DLFP50N18L-A	Y50-N18L-A、 YB50-N18L-AT、 Y50-N18L-B	12.8	128	175	87 155
DLFP52113	51814、 51913、 52113、 53030	12.8	128	185	80 170
DLFP30L-BS	YIX30L、 YIX30L-BS、 YB30L-B、 GYZ32	12.8	160	166	124 175
DLFP30HL-BS	YIX30L、 YIX30L-BS、 YB30L-B、 YB30C	12.8	320	166	124 175
DLFP14HL-BS-H	GHD14HL-BS、 GYZ16HL	12.8	64	149	87 144
DLFP20H-BS-H		12.8	96	149	87 144
DLFP20HL-BS-H	GHD20HL-BS、 GYZ20HL	12.8	96	176	87 153
DLFP30HL-BS-H	GHD30HL-BS、 GYZ32HL	12.8	160	166	127 175

HL	Weight(kg)	Charge Current(A)	Assembly Figure	Terminal Type	CA
	0.5	0.045			
	0.6	0.09			
	0.6	0.09			
	0.7	0.09			
	0.6	0.125			
	0.7	0.125			
	1	0.15			
	1	0.15			
	0.9	0.15			
	0.9	0.15			
	1.1	0.18			
	1	0.18			
	1.1	0.18			
	1.1	0.18			
	1	0.25			
	1	0.25			
	1.2	0.25			
	1.2	0.25			
	1.2	0.25			
	1.2	0.25			
	1.4	0.27			
	1.5	0.27			
	1.7	0.375			
	1.9	0.375			
	1.7	0.375			
	1.7	0.375			
	2.1	0.5			
	2.1	0.5			
	2.1	0.5			
	2.5	0.625			
	2.6	0.625			
	4.1	1.25			
	1.2	0.25			
	1.2	0.25			
	1.7	0.375			
	2.6	0.625			

CCA/-18°C